

Dialog3G WINDRIVER™



Remote Small Concentrator



The WINDRIVER™ is a part of the Dialog3G™ AMI system, providing a data rich communications platform between the end point meters, boosters, repeaters and utility's communication server. Data flow is structured around three principal areas: Data Source (end point meters), Data Acquisition (the Components responsible for collecting and communicating the data boosters and repeaters), and Data Control - City mind data S/W.

The concentrator is capable of 2 way real time communication between the Concentrator and the Utility communication server. Remote network diagnostics is enabled between the utility communication server and the Concentrator. The unit can be programmed On-Site by Ethernet and serial ports; the unit is connected to the Backbone network via a Cellular Modem (Or any TCP/IP device).

The WINDRIVER™ box contains MMR transceiver for the 360° area coverage connected to directional antenna (according to application). The system is controlled by an embedded controller (Linux based), supported by an automatic resettable Relay unit to boot the system in case of power or communication failure. GPRS programmable gateway Cellular Modem, Offers quad-band GPRS connectivity, links the WINDRIVER™ to the fixed base system management network.

The WINDRIVER™ can support up to 50K meters.

The WINDRIVER™ Concentrator is powered by Mains AC supply (according to the country regulation and standards). Communications comply with FCC requirements.

Technical Specifications

Box Size	650mm x 400mm x 210mm Metal Grey Box (with locking key)
Weight	7.5 Kg
Power Supply	Mains Input: 240-120Vac 50/60Hz
Communication for On-Site programming (Connectors types)	Serial RS232, Ethernet 10/100 'Cat5' sealed caps
Antennas connections	N-type female + One TNC Cell Modem outlet
RF Range	Up to 2 Km coverage L.O.S (from Boosters and repeaters)
MMR- Rx Sensitivity	-102 dBm (BER 1E-3)
MMR- Rx Frequencies	916.3MHz Or 868.3MHz
MMR- Rx Modulation	FSK
GPRS Frequency Bands	850/900/1800/1900 MHz, Class 12
RF standards	FCC: Meets part 15 requirements
Environment	IP-65
Operating Temp.	-20c° to +60c°
Humidity	Max 95%
Lightning Protection	EMP Protector (50 Ohm 300W)



Arad Ltd.
Dalia 1923900, Israel, Tel: 972-4-9897911, Fax: 972-4-9897960, www.arad.co.il

